



David J. Cushing  
T 202-663-7925  
dcushing@sughrue.com

January 7, 2002

## BOX PCT

Commissioner for Patents  
Washington, D.C. 20231

PCT/FR00/01824  
-filed June 29, 2000

www.sughrue.com

Re: Application of Guillaume CALOT, Eric BOUDJEMA, Denis ROUFFET, Jean-Luc PALMADE, Pascal PIAU, Yves PELIGRY  
PROCEDE ET SYSTEME DE TELECOMMUNICATION PAR SATELLITES  
DEFILANTS DANS LEQUEL LES COMMUNICATIONS SONT  
TRANSFERABLES D'UN SATELLITE A UN AUTRE  
Assignee: **ALCATEL**  
Our Ref: Q67858

Dear Sir:

The following documents and fees are submitted herewith in connection with the above application for the purpose of entering the National stage under 35 U.S.C. § 371 and in accordance with Chapter II of the Patent Cooperation Treaty:

- ☐ an executed Declaration and Power of Attorney.
- ☐ an English translation of the International Application.
- ☒ a copy of the PCT Application as filed in French
- ☒ 3 sheets of drawings.
- ☐ an English translation of Article 19 claim amendments.
- ☐ an English translation of Article 34 amendments (annexes to the IPER).
- ☐ an executed Assignment and PTO 1595 form.
- ☒ a Form PTO-1449 listing the ISR references, and a complete copy of each reference.
- ☐ a Preliminary Amendment

The Declaration and Power of Attorney, English translation of the International Application, Assignment, Preliminary Amendment will be submitted at a later date.

It is assumed that copies of the International Application, the International Search Report, the International Preliminary Examination Report, and any Articles 19 and 34 amendments as required by § 371(c) will be supplied directly by the International Bureau, but if further copies are needed, the undersigned can easily provide them upon request.

The Government filing fee is calculated as follows:

100-19937 10/019937  
JC13 Rec'd PCT/PTO 07 JAN 2002  
2100 Pennsylvania Avenue, NW  
Washington, DC 20037-3213  
T 202.293.7060  
F 202.293.7860

1010 El Camino Real  
Menlo Park, CA 94025-4345  
T 650.325.5800  
F 650.325.6606

Toei Nishi Shimbashi Bldg. 4F  
13-5 Nishi Shimbashi 1-Chome  
Minato-Ku, Tokyo 105-0003  
Japan  
T 03.3503.3760  
F 03.3503.3756



SUGHRUE MION, PLLC

Commissioner for Patents  
 Washington, D.C. 20231  
 Attorney Docket Q67858  
 Page 2  
 January 4, 2002


Total claims	<u>25</u>	-	<u>20</u>	=	<u>5</u>	x	\$18.00	=	<u>\$90.00</u>
Independent claims	<u>1</u>	-	<u>3</u>	=		x	\$84.00	=	<u>\$0.00</u>
Base Fee									<u>\$890.00</u>
<b>TOTAL FEE</b>									<u><b>\$980.00</b></u>

A check for the statutory filing fee of \$980.00 is attached. You are also directed and authorized to charge or credit any difference or overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16, 1.17 and 1.492 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Priority is claimed from:

<u>Country</u>	<u>Application No</u>	<u>Filing Date</u>
France	9908843	July 8, 1999

Respectfully submitted,

  
 David J. Cushing  
 Registration No. 28,703

SUGHRUE MION, PLLC  
 2100 Pennsylvania Avenue, N.W.  
 Washington, D.C. 20037-3213  
 Telephone: (202) 293-7060  
 Facsimile: (202) 293-7860

Date: January 7, 2002

**PATENT APPLICATION**  
**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re application of

PCT/FR00/01824

Guillaume CALOT, et al.

Attorney Docket No. Q67858

Appln. No.: 10/019,937

Group Art Unit: Not Assigned

Confirmation No.: 8753

Examiner: Not Assigned

Filed: January 07, 2002

For: A TELECOMMUNICATIONS METHOD AND SYSTEM USING  
NONGEOSYNCHRONOUS SATELLITES AND IN WHICH CALLS CAN BE  
HANDED OVER FROM ONE SATELLITE TO ANOTHER

**PRELIMINARY AMENDMENT**

Commissioner for Patents  
Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

**IN THE CLAIMS:**

**Please enter the following amended claims:**

3. (Amended) A method according to claim 1, characterized in that call handovers are commanded collectively for a plurality of terminals.

6. (Amended) A method according to claim 4, characterized in that the handover times are distributed so that the resources used by each satellite are substantially the same.

7. (Amended) A method according to claim 1, characterized in that the times of

PRELIMINARY AMENDMENT  
Appln. No. 10/019,937

handover of calls from one satellite to another are predefined for each terminal.

9. (Amended)A method according to claim 7, characterized in that a call is handed over to another satellite ahead of time if said other satellite provides a communication capacity greater than that of the former satellite.

10. (Amended)A method according to claim 1, characterized in that the terrestrial areas (20<sub>i</sub>) are fixed.

11. (Amended)A method according to claim 1, characterized in that the resources allocated to a terminal for a satellite include a carrier frequency and a plurality of codes, especially Hadamard sequences, and/or time slots.

12. (Amended)A method according to claim 1, characterized in that a single system (72) for allocating resources (74) is provided in each terminal and/or the management station and said resources are duplicated during a handover period.

14. (Amended)A method according to claim 12, characterized in that zero power is allocated to signals on the second path before handover and zero power is allocated to signals on the first path after handover.

PRELIMINARY AMENDMENT  
Appln. No. 10/019,937

16. (Amended)A method according to claim 12, characterized in that the powers allocated to the duplicated cells or packets are monitored.

20. (Amended)A terminal according to claim 17, characterized in that it includes two directional antennas, one intended to be pointed toward one satellite and the other toward another satellite.


25. (Amended)A management station according to claim 22, characterized in that it includes a system for allocating the terminals carrier frequencies divided into non-contiguous subsets, two carriers from the same subset being chosen to hand over a call from one satellite to another.

PRELIMINARY AMENDMENT  
Appln. No. 10/019,937

**REMARKS**

Entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,



David J. Cushing  
Registration No. 28,703

SUGHRUE MION, PLLC  
2100 Pennsylvania Avenue, N.W.  
Washington, D.C. 20037-3213  
Telephone: (202) 293-7060  
Facsimile: (202) 293-7860

Date: April 17, 2002

**APPENDIX**

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

**IN THE CLAIMS:**

**The claims are amended as follows:**

3.     ~~(Amended)~~A method according to ~~claim 1 or claim 2~~claim 1, characterized in that call handovers are commanded collectively for a plurality of terminals.

6.     ~~(Amended)~~A method according to ~~claim 4 or claim 5~~claim 4, characterized in that the handover times are distributed so that the resources used by each satellite are substantially the same.

7.     ~~(Amended)~~A method according to ~~any preceding claim~~claim 1, characterized in that the times of handover of calls from one satellite to another are predefined for each terminal.

9.     ~~(Amended)~~A method according to ~~claim 7 or claim 8~~claim 7, characterized in that a call is handed over to another satellite ahead of time if said other satellite provides a communication capacity greater than that of the former satellite.

10.    ~~(Amended)~~A method according to ~~any preceding claim~~claim 1, characterized in that the terrestrial areas (20<sub>i</sub>) are fixed.

PRELIMINARY AMENDMENT  
Appln. No. 10/019,937

11. (Amended)A method according to ~~any preceding claim~~claim 1, characterized in that the resources allocated to a terminal for a satellite include a carrier frequency and a plurality of codes, especially Hadamard sequences, and/or time slots.

12. (Amended)A method according to ~~any preceding claim~~claim 1, characterized in that a single system (72) for allocating resources (74) is provided in each terminal and/or the management station and said resources are duplicated during a handover period.

14. (Amended)A method according to ~~claim 12 or claim 13~~claim 12, characterized in that zero power is allocated to signals on the second path before handover and zero power is allocated to signals on the first path after handover.

16. (Amended)A method according to ~~any one of claims 12 to 15~~claim 12, characterized in that the powers allocated to the duplicated cells or packets are monitored.

20. (Amended)A terminal according to ~~any one of claims 17 to 19~~claim 17, characterized in that it includes two directional antennas, one intended to be pointed toward one satellite and the other toward another satellite.

25. (Amended)A management station according to ~~any one of claims 22 to 24~~claim



PRELIMINARY AMENDMENT  
Appln. No. 10/019,937

22, characterized in that it includes a system for allocating the terminals carrier frequencies divided into non-contiguous subsets, two carriers from the same subset being chosen to hand over a call from one satellite to another.

A TELECOMMUNICATIONS METHOD AND SYSTEM USING NON-  
GEOSYNCHRONOUS SATELLITES AND IN WHICH CALLS CAN BE  
HANDED OVER FROM ONE SATELLITE TO ANOTHER

5 The invention relates to a telecommunications method  
and system using non-geosynchronous satellites.

Until recently, satellites used for  
telecommunications have mainly been geosynchronous  
satellites. This has two drawbacks, however: firstly  
10 terrestrial coverage that is relatively limited and,  
secondly, and more importantly, signal propagation time  
that is not always compatible with real-time  
communications. Because the altitude of a geosynchronous  
satellite is 36 000 km, the minimum time for a signal to  
travel from the Earth to the satellite and from the  
15 satellite to the Earth is approximately 250 ms. Also,  
free space propagation losses over this distance are not  
favorable to achieving high capacity.

To increase the coverage of systems using relay  
satellites and, more importantly, to reduce the  
20 propagation time, telecommunications systems have been  
developed using a constellation of satellites in low  
Earth orbit or in medium Earth orbit. The altitudes of  
the orbits of such satellites are from 800 to 1 500 km  
and the orbits are chosen so that practically all of the  
25 surface of the Earth is covered, i.e. so that at any time  
at least one satellite can be seen from anywhere on the  
Earth (with the exception of polar areas on a few  
occasions).

Because the satellites are not geosynchronous, from  
30 any point on the Earth the same satellite can be seen for  
only a limited time period, at most of the order of 15  
minutes. Because of this, the telecommunications system  
is designed so that, for a terrestrial user, as one  
satellite leaves the area of visibility there is another  
35 satellite ready to take over the call.

Transferring a call from one satellite to another is  
sometimes referred to as "handing over" or "handing off"

the call.

In prior art non-geosynchronous satellite telecommunications systems used until now, handover is effected individually for each terminal. To this end, means for detecting call quality, for example the signal-to-noise ratio, between the terminal and the satellites in view are provided in each terminal, i.e. in each equipment unit designed to receive and send calls. Control or management means, located in a central station, for example, command the handover of calls sent and received by the terminal from a first satellite to a second satellite when the quality of calls relayed by the first satellite falls below a pre-determined threshold and when the quality of calls relayed by the second satellite is above that threshold.

The invention stems from the observation that this type of handover, effected individually for each terminal, causes difficult problems in managing the allocation of call resources. Call resources in a telecommunications system are intrinsically limited and must be managed continuously so that the system can handle the maximum data or calls.

The term "resources" refers to the power of the transmitter and to the characteristics of the transmitted signals for allowing a large number of simultaneous calls at all times. These characteristics of the signals can be their polarization, different carrier frequencies, time division multiplexing, and various codes. All this is known in the art. Multiplexing in time is known as time division multiple access (TDMA) and separating signals by means of their codes is known as code division multiple access (CDMA).

Accordingly, on each handover of a call involving one terminal from one satellite to another, the telecommunications system must reapportion its resources, using a complex program, in particular because at the time of the handover practically all the parameters of a

call (power, carrier frequency, time and/or code and polarization), are liable to change. The complexity of managing all this naturally increases as the number of users of the telecommunications system increases.

5           The invention remedies these drawbacks.

          It is characterized in that, the telecommunications system being such that the communication domain is divided into terrestrial areas, inside each area the periods of handover of stationary (fixed) terminals in  
10       the area is commanded using predetermined data concerning the times during which at least two satellites are simultaneously visible in the area or in a portion of the area. For example, one satellite is moving away from the area and the other is approaching said area.

15           In other words, the invention exploits the deterministic (i.e. known in advance) character of the orbits of the satellites and the times at which they are pointed toward the area concerned.

          Call handover can therefore be managed collectively,  
20       to distribute call resources optimally. What is more, as the period of common visibility of the two satellites is known in advance, there is no need for continuous monitoring of the presence of a second satellite.

          The invention is particularly useful in the case of  
25       a telecommunications system for which the terrestrial areas are fixed, rather than mobile, since in this case the number of handovers to be effected simultaneously is large.

          One embodiment, in which the terminals and/or the  
30       central station and/or the satellites include directional antennas, exploits predefined data concerning the times at which at least two satellites are simultaneously visible in the area, or in a portion of the area, in order to point a second antenna or a second set of  
35       antennas toward the satellite that will take over the calls.

          It should be noted that, if directional antennas are

used, the same frequencies can be used simultaneously in the same terminal or in the same central station if the two satellites transmit beams with sufficient angular separation.

5           In one embodiment the periods of handover from one satellite to another are commanded so that they can be distributed over all the terminals during the period of double visibility. It is therefore possible to  
10           distribute over this period the processing power necessary to effect the handovers and the corresponding exchanges of signaling between the terminals and the network.

          In one embodiment, the individual handover periods are distributed so that the resources used by each  
15           satellite remain substantially constant at all times.

          Pre-programmed distribution of handovers can be combined with real-time management of calls on an individual basis.

          In some particular circumstances it may be necessary  
20           to depart from the collective handover period for each terminal. For example, a link for a terminal or a set of terminals may fail because of an obstacle on the propagation path between the terminal and the satellite.

          Traffic peaks can also occur, for example, leading  
25           to the temporary need for a distribution of resources between satellites departing from the pre-programmed distribution. Nevertheless, as this possibility of departure from the pre-programmed management scheme occurs relatively infrequently, pre-programmed management  
30           retains all of the advantages referred to above.

          In another aspect, that can be used independently of its aspects mentioned above, the invention provides features facilitating handover of calls from one satellite to another.

35           A first of these features consists of dividing all the carrier frequency resources into non-contiguous subsets such that, when a call is handed over from one

satellite to another, the carrier resources of the two calls belong to the same subset.

Thus grouping the carriers into subsets significantly facilitates call handover management and the design of the management station provided in each area. The management station includes a switch, as it were, for allocating carriers, and separating the carriers into subsets means that the switch can be divided into the same number of switching units as there are subsets. In this way each switching unit is of simpler design than a switching unit having to process all the carriers simultaneously.

In an aspect that can also be used independently of its other aspects described above, the invention relates to the level at which the data of a call is separated in order to effect the handover.

The level at which the data of a call is separated in order to effect handover from one satellite to another is preferably downstream of the multiplexing of the cells (more generally, the multiplexing of the user signals), in which case calls are handed over from a carrier provided for one satellite to another carrier provided for another satellite. The handover is particularly simple to effect and the handover method is very suitable for handing over a multiplicity of calls.

Multiplexing cells or packets consists of distributing the cells or packets between frames including 16 time slots, a time slot corresponding to the duration of a cell. A plurality of cells is sent in each time slot. The various cells that are allocated to the same time slot are distinguished from each other by a resource, for example their code, their time slot or their carrier frequency.

It is assumed hereinafter that the cells or packets are distinguished from each other by their code and/or their time slot.

When handover is effected downstream of

multiplexing, a single mechanism is provided for allocating resources to cells. However, power control must be implemented on each path, because the attenuation can differ from one path to another.

5           With the above type of handover, it may be preferable to provide for simultaneous sending on the two paths during a cell time slot. This transition period is exploited to adjust the power on the new path because (the resources being the same on the two paths), before  
10       handover the cells of the current frame are sent at a given power on the first path and at zero power on the second path and after handover the cells are sent at zero power on the first path. Thus it is preferable to ensure a gentle transition in terms of the power resource on the  
15       two paths. This being the case, during the transition period, the resources must be duplicated, one carrier frequency being allocated to one path and another carrier frequency to the other path. What is more, given that the cells are allocated collectively for the two paths,  
20       it is also necessary to satisfy an additional condition, namely that the sum of the powers of the cells must not exceed the authorized maximum power on each path during the same cell time slot.

25           This being so, the handover time clearly depends on the location of the terminal.

          The invention generally provides a telecommunications method using non-geostationary Earth satellites and in which the Earth is divided into areas inside which calls involving fixed (stationary) terminals  
30       in said area are relayed by a management station and each terminal and the management station communicate via a satellite, another satellite taking over a call when the former satellite is no longer used, which telecommunications method is characterized in that  
35       commanding handover of calls from one satellite to another makes use of predetermined times during which at least two satellites are simultaneously visible from the

area or from a portion of the area.

In one embodiment handover of calls involving the terminals from one satellite to another is commanded from the management station.

5        Call handovers are preferably commanded collectively for a plurality of terminals.

10        In one embodiment, in determining the handover time for each terminal, allowance is made for the power available and/or the availability of communication resources.

In one embodiment handover times are commanded so that they can be distributed over all the terminals during the period of double visibility of the satellites.

15        In one embodiment the handover times are distributed so that the resources used by each satellite are substantially the same.

The times of handover of calls from one satellite to another are predefined for each terminal, for example.

20        In one embodiment call quality is monitored for each terminal and a call is handed over to another satellite ahead of time if the call quality for a terminal falls below a predetermined threshold, for example because of masking.

25        In one embodiment a call is handed over to another satellite ahead of time if said other satellite provides a communication capacity greater than that of the former satellite.

The terrestrial areas are preferably fixed.

30        In one embodiment the resources allocated to a terminal for a satellite include a carrier frequency and a plurality of codes, especially Hadamard sequences, and/or time slots.

35        In one embodiment a single system for allocating resources is provided in each terminal and/or the management station and said resources are duplicated during a handover period.

In one embodiment two cells, packets or other



signals to be relayed simultaneously by two different satellites have different carrier frequencies and preferably the same codes.

5 In one embodiment zero power is allocated to signals on the second path before handover and zero power is allocated to signals on the first path after handover.

In one embodiment non-zero powers are allocated to both sets of cells or packets during a transition period, for example equal to a cell or packet time slot.

10 In one embodiment the powers allocated to the duplicated cells or packets are monitored.

The present invention further provides a terminal for a telecommunications system using non-geosynchronous Earth satellites and in which terrestrial areas are defined, each terminal in an area communicating with the telecommunications system via a management station in that area, calls between the management station and the terminal being relayed via a satellite, and means being provided in each terminal for commanding handover of calls from one satellite to another satellite, which terminal is characterized in that handover means in said terminal include means for receiving handover command signals.

25 In one embodiment the means for commanding handover make use of predetermined times at which at least two satellites are simultaneously visible in the area or in a portion of the area.

30 In one embodiment the terminal includes means for measuring the quality of the link to each satellite and means for bringing handover forward if the quality of the link to the satellite that is moving away falls below a predetermined threshold.

35 In one embodiment the terminal includes two directional antennas, one intended to be pointed toward one satellite and the other toward another satellite.

In one embodiment signals for commanding handover include signals for commanding pointing ahead of time of

the antenna intended to be pointed toward the satellite due to take over the call.

The present invention also provides a management station for a communication system in which terrestrial areas are defined, each terminal in an area communicating with the telecommunications system via a management station in that area, calls between the management station and the terminals being relayed via a satellite, and means being provided in each terminal for commanding handover of calls from a first satellite to a second satellite, which management station is characterized in that it includes means for commanding handover of calls involving stationary terminals in the area; or in a portion of the area, using predetermined times at which at least two satellites are visible simultaneously in that area or in a portion of that area.

In one embodiment the management station includes means for determining individual handover times for each terminal as a function of the allocation of power and/or communication resources.

In one embodiment the periods of handover from one satellite to another are commanded so that they can be distributed over all of the terminals during the period of double visibility.

In one embodiment the management station includes a system for allocating the terminals carrier frequencies divided into non-contiguous subsets, two carriers from the same subset being chosen to hand over a call from one satellite to another.

Other features and advantages of the invention will become apparent from the following description of embodiments of the invention, which is given with reference to the accompanying drawings, in which:

Figure 1 is a diagram of a telecommunications system to which the invention applies,

Figures 2a to 2f are diagrams showing various instances of satellite visibility and periods of

handovers effected by the method according to the invention,

Figure 3a shows an area of a system of the Figure 1 type, indicating beams transmitted by a plurality of satellites,

Figure 3b is a diagram analogous to those of figures 2a to 2f and corresponding to the situation shown in Figure 3a,

Figure 4 is a diagram showing one example of the method of programming beams transmitted by send/receive means on board satellites of the Figure 1 system,

Figure 5 is a diagram showing one example of a carrier frequency distribution used in the method according to the invention,

Figure 6 is a diagram of a management station of the Figure 1 system employing the method shown in Figure 5, and

Figure 7 is a diagram showing one example of the level at which handover can be effected in a terminal or a management station.

The embodiment of the invention described next with reference to the figures relates to a telecommunications system using a constellation of satellites orbiting the Earth at an altitude of approximately 1 450 km. The terrestrial surface is divided into substantially circular areas with a diameter of 700 km. Within each area 20<sub>i</sub> (Figure 1) is a management station 22, which is located at the center of the area, for example, and a plurality of terminals 24<sub>1</sub>, 24<sub>2</sub>, 24<sub>3</sub>, 24<sub>4</sub>, etc. The management station 22 is connected to a terrestrial or other type of communication network (not shown).

All the calls sent or received by a terminal 24<sub>i</sub> pass through the management station 22 and calls between each terminal and the station 22 are relayed by a satellite S<sub>1</sub> or S<sub>2</sub>. In other words, in the example shown in Figure 1, a call between a terminal 24<sub>i</sub> and a user or the network to which the station 22 is connected is

relayed by a satellite  $S_1$  or  $S_2$  and passes through the management station 22; a call between a terminal  $24_1$  and another terminal  $24_3$  or  $24_4$  remote from the terminal  $24_1$  is relayed by the satellite  $S_1$ , passes through the station 22 and is relayed by the satellite  $S_2$  or  $S_1$ .

Equipment (not shown) activated on a pre-programmed basis is provided on each satellite for receiving and forwarding calls. In one example, each satellite has control means such that several terrestrial areas are "illuminated" at a time, and the control process is such that, as it moves, the satellite modifies the beam so that it always impinges on the area concerned during the satellite's active transit across the area. The maximum duration of this transit is approximately 15 minutes.

Because the period of visibility of a satellite from a given area is limited, the constellation of satellites must be such that when one satellite is approaching the end of its period of visibility it is replaced by another satellite to take over the call. Because this type of telecommunications system is generally intended for high-quality calls, it is necessary to prevent the quality of the calls from being affected by handing the calls over from one satellite to another. In other words, the system is organized so that, at least at the time when a satellite relaying a call is about to leave the area of visibility, another satellite is simultaneously in the area of visibility and remains in it when the first one is no longer visible.

In one embodiment, satellite visibility is predetermined, as a function of the elevation of the satellite relative to the management station 22 and to each terminal  $24_i$ . The minimum elevation for the management station to be able to see a satellite is  $5^\circ$  and the minimum elevation for a terminal to be able to see a satellite is  $10^\circ$ . In this embodiment, because of the dimensions of the area and the altitude of the satellites, all the terminals  $24_i$  in the area can see a

satellite when it has an elevation of  $14.4^\circ$  relative to the station 22. On the other hand, none of the terminals can see the satellite when its elevation relative to the station 22 is less than  $6.1^\circ$ .

5           Accordingly, only a portion of the area  $20_i$  can see the satellite when the elevation of the satellite relative to the station 22 is from  $6.1^\circ$  to  $14.4^\circ$ .

          Given the high cost of each satellite and its onboard equipment, the number of satellites must be  
10   limited. For this reason it is generally not possible, in all the areas  $20_i$ , when the elevation one satellite relative to the management station is beginning to decrease toward  $14.4^\circ$ , for another satellite to have an  
15   elevation relative to the same station of at least the same value, and to retain that minimum elevation, or a greater elevation, after the elevation of the setting satellite has fallen below  $14.4^\circ$ . In other words, it is not always possible to provide for a satellite visible to  
20   all the terminals in the area to be replaced immediately by another satellite visible to all the terminals in the area.

          In fact, as explained later, very diverse situations can arise during which the mechanisms for effecting handover from one satellite to another must intervene.  
25   The telecommunications system must nevertheless take account of all these possibilities in commanding the turning on or activation of the sending and receiving means on board each satellite.

          The invention optimizes the management of  
30   communication resources at all times by exploiting this system management function to command the handing over of calls from one satellite to another.

          To this end, handover of calls from each terminal and/or each management station is effected by a control  
35   system which is centralized in the management station and which decides on handovers as a function of pre-programmed activation of the sending and receiving means

on board each satellite.

Thus management of call resources can be balanced during handover.

For handover purposes, each terminal has two  
5 directional antennas, one of which is pointed toward the current satellite and the other of which, prior to handover, is pointed toward the satellite that is due to take over the call.

Note that in the above telecommunications system, in  
10 which the pencil beams transmitted by the satellites are fixed on the terrestrial areas, handover must be effected simultaneously for a large number of terminals and during a relatively short time period. Also, the need for handover is not regularly distributed in time, but  
15 sporadic.

Figures 2a to 2f show various situations of handing over calls from one satellite to another. In each diagram, each line represents the elevation of a satellite as a function of time  $t$ . A continuous line  
20 corresponds to a satellite whose elevation relative to the management station is greater than  $14.4^\circ$  and a dashed line corresponds to an elevation relative to the management station from  $6.1^\circ$  to  $14.4^\circ$ .

In the Figure 2a example, there is a period  $T_1$  in  
25 which the elevation of both satellites  $S_1$  and  $S_2$  is greater than  $14.4^\circ$ . However, in this system calls are handed over from the setting satellite  $S_1$  to the rising satellite  $S_2$  in a portion  $T_{gw}$  of the period  $T_1$ .

The handover of calls is commanded from the  
30 management station of the area, for example. In this case, handover from the satellite  $S_1$  to the satellite  $S_2$  is commanded for all the terminals of the area during the time  $T_{gw}$ .

This collective command optimizes management of the  
35 distribution of communication resources and power, as much with regard to the terminals of the area as with regard to the satellites and the whole of the

telecommunications system. Handover for the various terminals can be uniformly distributed over the period  $T_{gw}$ , for example.

In the example, each terminal has two mobile  
5 directional antennas for tracking the satellites. One of the two antennas is not used outside handover periods. The unused antenna is pointed toward the satellite  $S_2$  in advance of handover.

In the situation shown in Figure 2b, the setting  
10 satellite  $S_1$  has an elevation from  $6.1^\circ$  to  $14.4^\circ$  in a period  $T_2$  during which the rising satellite  $S_2$  has an elevation greater than  $14.4^\circ$  and the satellites  $S_1$  and  $S_2$  both have an elevation greater than  $14.4^\circ$  during a period  $T_d$  preceding the period  $T_2$ . In this case, handover can be  
15 effected during a period  $T_{gw}$  equal to the sum of the periods  $T_d$  and  $T_2$ .

Note that during the period  $T_d$  the terminals for which handover of calls from the satellite  $S_1$  to the satellite  $S_2$  is commanded are at least those for which the  
20 satellite  $S_1$  has an insufficient elevation during the period  $T_2$ .

The situation shown in Figure 2c is analogous to that shown in Figure 2b. It differs therefrom only in that the rising satellite  $S_2$  has a period  $T_3$  at the  
25 beginning of its period of visibility from the area during which its elevation is from  $6.1^\circ$  to  $14.4^\circ$ . Both satellites have an elevation greater than  $14.4^\circ$  during a period  $T'_d$  at the end of the period of visibility of the satellite  $S_1$ . The period  $T_{gw}$  for commanding handover  
30 comprises a portion of the period  $T_3$  and the period  $T'_d$ .

Thus in the example shown in Figure 2d there is no period during which both satellites  $S_1$  and  $S_2$  simultaneously have an elevation greater than  $14.4^\circ$ . On the other hand, both satellites are visible at all times  
35 from the management station during a period  $T_{gw}$  that includes a first period  $T_4$  during which the satellite  $S_1$  has an elevation greater than  $14.4^\circ$  relative to the

management station, although the satellite  $S_2$  has an elevation less than  $14.4^\circ$  (but greater than  $6.1^\circ$ ). During the second period  $T_5$  both satellites have elevations from  $6.1^\circ$  to  $14.4^\circ$  and, finally, during the third period  $T_6$ , the elevation of the satellite  $S_1$  is from  $6.1^\circ$  to  $14.4^\circ$  and that of the satellite  $S_2$  is greater than  $14.4^\circ$ . In this case, as in Figures 2b and 2c, handover can be effected progressively for the various terminals.

In the example shown in Figure 2e, there is no period of common visibility for handing over all the calls from the setting satellite  $S_1$  to the rising satellite  $S_2$ .

In this case a third satellite  $S_3$  is used which, in this example, has an elevation from  $6.1^\circ$  to  $14.4^\circ$  during the handover period  $T_{ho}$ . Also, the visibility of the satellites  $S_1$ ,  $S_2$  and  $S_3$  from the area is such that during a period  $T_{gw1,2}$  calls are handed over from the satellite  $S_1$  to the satellite  $S_2$  for the terminals in the portion of the area from which the satellite  $S_2$  and the satellite  $S_1$  are visible and from which the satellite  $S_2$  will remain visible.

During a period  $T_{gw1,3}$  which, in this example, coincides with the greater portion of the period  $T_{gw1,2}$ , calls are handed over from the satellite  $S_1$  to the satellite  $S_3$  for terminals in the remaining portion of the area, from which both satellites are visible. In this case, of course, the satellite  $S_3$  remains visible from the remaining portion of the area up to the start of the period in which the satellite  $S_2$  has an elevation greater than  $14.4^\circ$ . Calls involving these terminals are handed over from the satellite  $S_3$  to the satellite  $S_2$  during a period  $T_{gw3,2}$  which, in this example, is separate from the periods  $T_{gw1,2}$  and  $T_{gw1,3}$ .

In the example shown in Figure 2f, handover from a satellite  $S_1$  to a satellite  $S_4$  during a period  $T_{ho}$  involves two other satellites  $S_2$  and  $S_3$ . Various portions of the zone are handed over first from the satellite  $S_1$  to the



satellite  $S_2$  during a period  $T_{gw1,2}$  and another portion of the zone is handed over from the satellite  $S_1$  to the satellite  $S_3$  during a period  $T_{gw1,3}$ . Handover from the satellite  $S_2$  to the satellite  $S_4$  and from the satellite  $S_3$  to the satellite  $S_4$  is effected during respective periods  $T_{gw2,4}$ ,  $T_{gw3,4}$ .

To explain more clearly the various situations that can arise in a terrestrial area, Figure 3a shows an area 20 and the tracks of the beams from the antennas of the three satellites  $S_1$ ,  $S_2$  and  $S_3$  across the area and in its vicinity. Figure 3b is a diagram showing the visibility of the satellites in a form analogous to the diagrams of Figures 2a to 2f.

In the situation shown in Figure 3a, the beam from the antennas of the rising satellite  $S_2$  occupies the portion of the area 20 that is on the concave side of a line 30 representing the edge of the beam transmitted by the satellite  $S_2$ . Also, at this time, the satellite  $S_1$  is illuminating the portion of the area 20 that is on the concave side of a line 32. Thus it can be seen that, in this situation, there is a region 34 that is covered neither by the satellite  $S_1$  nor by the satellite  $S_2$ , but is covered by the satellite  $S_3$ , the edge of whose beam is represented by a line 36.

The arrows  $f_1$ ,  $f_2$  and  $f_3$  correspond to the direction of movement of the respective satellites  $S_1$ ,  $S_2$  and  $S_3$ . Clearly, calls involving the corresponding terminals have been handed over to the satellite  $S_3$  before the region 34 is no longer covered by the beam from the satellite  $S_1$ , and afterwards, when the region 34 is covered by the beam from the satellite  $S_2$ , calls involving the terminals in this region are handed over to the satellite  $S_2$ .

In the Figure 4 diagram, the horizontal segments each represent a period of visibility of a particular satellite from an area. In practice, the equipment on board the satellites is controlled so that it illuminates the corresponding area over the periods indicated.

The diagram represents scheduling based on a period of thirty hours and effected in the management station, for example.

5 In this diagram, the various segments, i.e. the various passages of the satellites over the area concerned, have been grouped into three sets  $E_1$ ,  $E_2$  and  $E_3$ . Each set constitutes a path enabling continuity of calls in time, as it were, despite the appearance and disappearance of the satellites.

10 In the set  $E_1$ , each call can be handed over from one satellite to the next. Likewise in the set  $E_2$ . In contrast, in the set  $E_3$ , there are portions of the area in which terminals cannot be handed over from one satellite of the set to another satellite of the same set. This  
15 applies to handover from the satellite  $S_5$  to the satellite  $S_6$ , for example. In this case, calls involving terminals that cannot be handed over from the satellite  $S_5$  to the satellite  $S_6$  are handed over from the satellite  $S_5$  to the satellite  $S_7$ , from the set  $E_1$  (arrow F) and calls involving  
20 those terminals continue in the set  $E_1$ .

To balance the load, it is then possible to hand over to the path  $E_3$  calls involving terminals that are allocated to the path  $E_1$ , which calls can then, of course, given the geographical position of the terminals, be  
25 handed over from the satellite  $S_5$  to the satellite  $S_6$  (arrow F').

Similarly, in the set  $E_3$  handover of calls from the satellite  $S_8$  to the satellite  $S_9$  is not possible for all the terminals. For this reason, and in an analogous  
30 fashion, calls involving terminals that cannot be handed over from the satellite  $S_8$  to the satellite  $S_9$  are handed over to a satellite  $S_{10}$  of the set  $E_2$  (arrow  $F_1$ ). Other calls are handed over from the satellite  $S_{10}$  to the satellite  $S_8$  (arrow  $F'_1$ ).

35 Call handover from one satellite to another for various terminals inside the area is made possible by the predetermined programming of the beams on board the

satellites, reflecting the deterministic nature of the trajectories of the satellites, both in space and in time.

Although the invention exploits the deterministic nature of the trajectory of the satellites and of the control of the equipment on board the satellites, it is not incompatible with individual management of handover to solve particular or temporary problems of certain terminals. For example, should a terminal normally intended to communicate via a given satellite be unable to do so at a particular time because of masking, for example because of a building or an unexpected obstacle in the field of the antenna, or because of bad weather, the call can be switched to another satellite and the control system in the management station 22 can take account of the masking that has been detected and subsequently hand over the call to satellites that are not masked.

Consider another example: should the call capacity (expressed in megabits/second) of the satellite allocated to a terminal be insufficient at a particular time, because of a momentary overload at the terminal, calls can temporarily be handed over to another satellite having a greater call capacity. It is also possible to bring forward the handover to the next satellite, if it provides a greater call capacity.

Another feature of the invention is described next with reference to Figures 5 and 6, namely distribution of the resources between satellites allocated to an area 20 in a manner that simplifies the implementation of the management station 22.

Before proceeding with this description, it is as well to bear in mind that in a telecommunications system according to the invention all terminals must be able to communicate with each other via the management station and must also be able to communicate with the terminals of a terrestrial or other network connected to the

management station 22. Also, each call or each packet must be able to utilize any resource of the network, i.e. any carrier frequency of any satellite.

5 This constraint causes difficult resource management problems.

To solve these problems in a manner that simplifies management by the station 22 (see above), the set of carriers available to the telecommunications system is divided into a plurality of subsets or bundles  $B_1, B_2, B_3$  (Figure 5), etc. so that handover from one satellite to another satellite of calls involving a terminal or the management station can be effected only by handing over the calls from a carrier of one subset to another carrier of the same subset. In this way a terminal is associated with only one subset of carriers.

Figure 5 symbolizes by means of rectangles the resources  $B_1$  for a terminal  $20_i$ . The figure shows that, in this case, three satellites  $S_1, S_2$  and  $S_3$  are visible from the terminal  $20_i$ , which is allocated the subset  $B_1$  including the carriers  $P_1$  to  $P_q$ . The carriers  $P_1$  to  $P_n$  are allocated to the satellite  $S_1$ , the carriers  $P_{n+1}$  to  $P_p$  are allocated to the satellite  $S_2$  and the carriers  $P_{p+1}$  to  $P_q$  are allocated to the satellite  $S_3$ .

Each of the satellites  $S_1, S_2, S_3$  can also communicate using carrier frequencies that are not in the subset  $B_1$ , for example frequencies in the subset  $B_2$ . However, these sub-carriers will not be used for calls involving the terminal  $20_i$ , but for calls involving other terminals, such as the terminal  $20_j$ .

Accordingly, when a call involving the terminal  $20_i$  which is relayed via the satellite  $S_1$  on the carrier frequency  $P_2$  must be handed over to the satellite  $S_2$ , the carrier frequency used for that call involving the terminal  $20_i$  when it is relayed via the satellite  $S_2$  is chosen from the carrier frequencies  $P_{n+1}$  to  $P_p$  in the subset  $B_1$ .

The management station 22 includes a system 42

(Figure 6) for switching traffic in the station 22 by processing its carriers. The system 42 is divided into the same number of portions  $42_1$ ,  $42_2$ , etc. as there are subsets  $B_1$ ,  $B_2$ , etc. The system 42 effects the handover of calls from one satellite to another and also provides the connection to other networks, for example terrestrial networks. Under these conditions, each portion  $42_1$ ,  $42_2$ ,  $42_3$  of the system 42 includes an input/output  $44_1$ ,  $44_2$ , etc. connected to the terrestrial network(s) and a plurality of inputs/outputs  $46_1$ ,  $48_1$ , etc. In each portion  $42_i$ , the number of inputs/outputs  $46_i$ ,  $48_i$  is equal to the number of carriers in the corresponding subset  $B_i$ .

Furthermore, the station 22 includes a number  $N$  of modems  $50_1$  to  $50_n$  equal to the number of carriers. Each modem is associated with an antenna  $52_1$ ,  $52_2$ , etc.

The inputs/outputs  $46_i$ ,  $48_i$ , etc. are connected to the modems  $50_1$ ,  $50_2$ , etc. via a switching matrix 60.

If, as shown here, calls involving a terminal  $20_i$  are relayed at a particular time by the satellite at which the antenna  $52_1$  is pointed and on the carrier from the subset  $B_1$  corresponding to the output  $46_1$  of the portion  $42_1$  of the system 42, and if the calls must be handed over to the satellite at which the antenna  $52_2$  is pointed, then, in the portion  $42_1$  of the system, the calls are handed over (arrow H0) from the input/output  $46_1$  to the input/output  $48_1$ , and the input/output  $48_1$  is connected by the matrix 60 to the modem  $50_2$  and therefore to the antenna  $52_2$ .

Clearly this organization of the carriers in subsets simplifies the organization of the system 42, which is made up of a set of portions or modules  $42_1$ ,  $42_2$ , etc. which are all similar to each other.

The invention also relates to the level at which call handover can be effected. This use of the term "level" refers to the fact that handover can be effected downstream of the buffer memories in which the ATM cells

are waiting, instead of upstream of it. In this embodiment, handover is effected after the allocation (multiplexing) of resources.

5 If handover is effected downstream of multiplexing, it is referred to as "physical" handover, because it occurs close to the physical transmission resources.

Accordingly, in the embodiment shown in Figure 7, a handover 82 is effected at the physical level, i.e. after multiplexing the cells. Thus a set of buffer memories 10 60, 62, ..., 66 and distributor means 72 for distributing the resources 74 are provided.

Call switching 82 from one path to another is effected directly downstream of allocation of the resources 74. In other words, the same codes and/or time 15 slots are allocated to each path. The carrier frequencies are different, however.

Each path has its own power control function, represented by a respective symbol  $84_1$  and  $84_2$ . The power required for each path is not necessarily the same.

20 To ensure correct transition from the power of one path to that of another path, it is preferable to provide a transition period, corresponding to a frame, for example, during which the same resources in terms of codes and/or time slots are allocated simultaneously to 25 both paths, with simultaneous sending of cells on both paths during a cell time slot. Prior to this transition period zero power is allocated to the second path and after this transition period zero power is allocated to the first path.

30 During the transition period, in which the cells are sent with a non-zero power simultaneously on both paths, it is necessary to monitor the power so that, for each path, the sum of the powers allocated to the cells does not exceed the maximum authorized power on that path. 35 Because this condition is difficult to satisfy, the call handover time is generally different from one terminal to another.

To explain more clearly the mechanism for handing over a call from one path to another, the operations to be effected are described briefly below.

5 It must first be borne in mind that each terminal has two antennas. Accordingly, during a handover preparation phase, the standby antenna of each terminal is pointed at the satellite due to take over the call. This pointing can be effected even before activating the pencil beam of the latter satellite.

10 The demodulator is synchronized to the frequency in time, phase, and frequency after turning on the pencil beam.

Finally, the quality of the link with the second satellite is estimated during this preparatory phase.

15 The preparatory phase is followed by a waiting phase during which the terminal waits for a handover or changeover instruction from the central station. This waiting phase can be terminated ahead of time if the quality of the link on the path of the first satellite is suddenly degraded, for example. In this case, the calls  
20 are switched quickly to the second path.

During a third phase, the central station issues the handover or changeover instruction to the terminal. The terminal acknowledges reception of the instruction and at  
25 the same time provides a precise indication of the quality of the link with the second satellite, and the power of the call is adjusted. The changeover is effected after this third phase.

## CLAIMS

1. A telecommunications method using non-geostationary Earth satellites ( $S_1$ ,  $S_2$ ,  $S_3$  and  $S_4$ ) and in which the Earth is divided into areas ( $20_i$ ) inside which calls involving  
5 terminals in said area are relayed by a management station (22) and each terminal ( $24_1$ ,  $24_2$ , etc.) and the management station communicate via a satellite, another satellite taking over a call when the former satellite is no longer used, characterized in that, the terminals  
10 being stationary, commanding handover of calls from one satellite to another makes use of predetermined times during which at least two satellites are simultaneously visible from the area or from a portion of the area.
- 15 2. A method according to claim 1, characterized in that handover of calls involving the terminals from one satellite to another is commanded from the management station (22).
- 20 3. A method according to claim 1 or claim 2, characterized in that call handovers are commanded collectively for a plurality of terminals.
4. A method according to claim 3, characterized in that,  
25 in determining the handover time for each terminal, allowance is made for the power available and/or the availability of communication resources.
5. A method according to claim 4, characterized in that  
30 handover times are commanded so that they can be distributed over all the terminals during the period of double visibility of the satellites.
6. A method according to claim 4 or claim 5,  
35 characterized in that the handover times are distributed so that the resources used by each satellite are substantially the same.



7. A method according to any preceding claim,  
characterized in that the times of handover of calls from  
one satellite to another are predefined for each  
5 terminal.

8. A method according to claim 7, characterized in that  
call quality is monitored for each terminal and a call is  
handed over to another satellite ahead of time if the  
10 call quality for a terminal falls below a predetermined  
threshold, for example because of masking.

9. A method according to claim 7 or claim 8,  
characterized in that a call is handed over to another  
15 satellite ahead of time if said other satellite provides  
a communication capacity greater than that of the former  
satellite.

10. A method according to any preceding claim,  
20 characterized in that the terrestrial areas (20<sub>i</sub>) are  
fixed.

11. A method according to any preceding claim,  
characterized in that the resources allocated to a  
25 terminal for a satellite include a carrier frequency and  
a plurality of codes, especially Hadamard sequences,  
and/or time slots.

12. A method according to any preceding claim,  
30 characterized in that a single system (72) for allocating  
resources (74) is provided in each terminal and/or the  
management station and said resources are duplicated  
during a handover period.

35 13. A method according to claim 12, characterized in that  
two cells, packets or other signals to be relayed  
simultaneously via two different satellites have

different carrier frequencies and preferably the same codes.

14. A method according to claim 12 or claim 13,  
5 characterized in that zero power is allocated to signals on the second path before handover and zero power is allocated to signals on the first path after handover.

15. A method according to claim 14, characterized in that  
10 non-zero powers are allocated to both sets of cells or packets during a transition period, for example equal to a cell or packet time slot.

16. A method according to any one of claims 12 to 15,  
15 characterized in that the powers allocated to the duplicated cells or packets are monitored.

17. A terminal for a telecommunications system using non-geosynchronous Earth satellites ( $S_1, S_2, S_3, S_4$ ) and in  
20 which terrestrial areas are defined, each terminal in an area communicating with the telecommunications system via a management station (22) in that area, calls between the management station and the terminal being relayed via a satellite, and means being provided in each terminal for  
25 commanding handover of calls from one satellite to another satellite, characterized in that, the terminal being stationary, handover means in said satellite include means for receiving handover command signals.

18. A terminal according to claim 17, characterized in  
30 that the means for commanding handover make use of predetermined times at which at least two satellites are simultaneously visible in the area or in a portion of the area.

19. A terminal according to claim 18, characterized in  
35 that it includes means for measuring the quality of the

link to each satellite and means for bringing handover forward if the quality of the link to the satellite that is moving away falls below a predetermined threshold.

5 20. A terminal according to any one of claims 17 to 19, characterized in that it includes two directional antennas, one intended to be pointed toward one satellite and the other toward another satellite.

10 21. A terminal according to claim 20, characterized in that signals for commanding handover include signals for commanding pointing ahead of time of the antenna intended to be pointed toward the satellite due to take over the call.

15 22. A management station for a telecommunications system in which terrestrial areas are defined, each terminal in an area communicating with the telecommunications system via a management station in that area, calls between the management station and the terminals being relayed via a satellite, and means being provided in each terminal for commanding handover of calls from a first satellite to a second satellite, which management station is  
20 characterized in that it includes means for commanding handover of calls involving stationary terminals in the  
25 area, or in a portion of the area, using predetermined times at which at least two satellites are visible simultaneously in that area or in a portion of that area.

30 23. A management station according to claim 22, characterized in that it includes means for determining individual handover times for each terminal as a function of the allocation of power and/or communication resources.

35 24. A management station according to claim 23, characterized in that periods of handover from one

satellite to another are commanded so that they can be distributed over all of the terminals during the period of double visibility.

- 5     25. A management station according to any one of claims  
22 to 24, characterized in that it includes a system for  
allocating the terminals carrier frequencies divided into  
non-contiguous subsets, two carriers from the same subset  
being chosen to hand over a call from one satellite to  
10 another.

## A B S T R A C T







A TELECOMMUNICATIONS METHOD AND SYSTEM USING NON-  
GEOSYNCHRONOUS SATELLITES AND IN WHICH CALLS CAN BE  
5 HANDED OVER FROM ONE SATELLITE TO ANOTHER

The invention relates to a telecommunications  
method using non-geostationary Earth satellites ( $S_1$ ,  $S_2$ ,  
 $S_3$  and  $S_4$ ) and in which the Earth is divided into areas  
10 ( $20_i$ ) inside which calls involving terminals in said area  
are relayed by a management station (22) and each  
terminal ( $24_1$ ,  $24_2$ , etc.) and the management station  
communicate via a satellite, another satellite taking  
over a call when the former satellite is no longer used.  
15 Handover of calls from one satellite to another is  
commanded by making use of predetermined times during  
which at least two satellites are simultaneously visible  
from the area or from a portion of the area. Call  
handovers are commanded collectively for a plurality of  
20 terminals, for example.


25

30

Translation of the title and the abstract as they were when originally filed by the  
35 Applicant. No account has been taken of any changes that may have been made  
subsequently by the PCT Authorities acting ex officio, e.g. under PCT Rules 37.2,  
38.2, and/or 48.3.




2/3




FIG\_2f


FIG\_3b





FIG\_3a




FIG\_4



3/3



FIG\_7





**DECLARATION AND POWER OF ATTORNEY FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)**

As a below named inventor, I hereby declare that: My residence, mailing address, and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention in the specification identified by Docket N°

**101983/SM/SSPD**

I hereby state that I have reviewed and understand the contents of the above identified application, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part application(s), material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or (f), or 365(b) of any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or 365(a) of any PCT international application(s) which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or any PCT international application(s) having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date	Priority Claimed	
			Yes	No
99 08 843	France	08 JULY 1999	<input type="checkbox"/>	<input type="checkbox"/>

I hereby claim domestic priority benefits under 35 United States Code §120 of any United States application(s), §119(e) of any United States provisional application(s), or §365(c) of any PCT International application(s) designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in a listed prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge my duty to disclose any information material to the patentability of this application as defined in 37 C.F.R. 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U.S. or International Application Number(s)	U.S. or International Filing Date	Status

I hereby appoint all attorneys of **SUGHRUE MION, PLLC** who are listed under the USPTO Customer Number shown below as my attorneys to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith, recognizing that the specific attorneys listed under that Customer Number may be changed from time to time at the sole discretion of Sughrue Mion, PLLC, and request that all correspondence about the application be addressed to the address filed under the same USPTO Customer Number.

**\*23373\***

**23373**

PATENT TRADEMARK OFFICE







I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

[Page 2 of 3 ]

<b>NAME OF SOLE OR FIRST INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Guillaume</b>		Family Name or Surname <b>CALOT</b>	
Inventor's Signature		Date <b>20/01/02</b>	
Residence: City <b>LE CHESNAY</b>	State	Country <b>FRANCE</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>15, avenue de Villars</b>			
City <b>LE CHESNAY</b>	State	Zip <b>78150</b>	Country <b>FRANCE</b>
<b>NAME OF SECOND INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Eric</b>		Family Name or Surname <b>BOUDJEMA</b>	
Inventor's Signature		Date <b>20/01/02</b>	
Residence: City <b>BOULOGNE</b>	State	Country <b>France</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>80, rue Marcel Dassault</b>			
City <b>BOULOGNE</b>	State	Zip <b>92100</b>	Country <b>FRANCE</b>
<b>NAME OF THIRD INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Denis</b>		Family Name or Surname <b>ROUFFET</b>	
Inventor's Signature		Date <b>20/01/02</b>	
Residence: City <b>BOULOGNE</b> <b>BILLANCOURT</b>	State	Country <b>France</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>16, rue Louis Pasteur</b>			
City <b>BOULOGNE</b> <b>BILLANCOURT</b>	State	Zip <b>92100</b>	Country <b>FRANCE</b>
<b>NAME OF FOURTH INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Jean-Luc</b>		Family Name or Surname <b>PALMADE</b>	
Inventor's Signature		Date <b>20/01/02</b>	
Residence: City <b>SAINT JORY</b>	State	Country <b>France</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>14A, Chemin de la Plaine</b>			
City <b>SAINT JORY</b>	State	Zip <b>31790</b>	Country <b>FRANCE</b>
<b>NAME OF FIFTH INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Pascal</b>		Family Name or Surname <b>PIAU</b>	
Inventor's Signature		Date <b>20/01/02</b>	
Residence: City <b>LACROIX</b> <b>FALGARDE</b>	State	Country <b>France</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>71, Route de la Gleyzette</b>			
City <b>LACROIX FALGARDE</b>	State	Zip <b>31120</b>	Country <b>FRANCE</b>
<b>NAME OF SIXTH INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Yves</b>		Family Name or Surname <b>PELIGRY</b>	
Inventor's Signature		Date <b>20/01/02</b>	


<b>NAME OF SOLE OR FIRST INVENTOR:</b>			
Given Name (first and middle [if any]) <u>Guillaume</u>		Family Name or Surname <u>CALOT</u>	
Inventor's Signature <u>[Signature]</u>		Date <u>X</u>	
Residence: City <u>LE CHESNAY</u>	State	Country <u>FRANCE</u>	Citizenship <u>FRENCH</u>
Mailing Address: <u>15, avenue de Villars</u>			
City <u>LE CHESNAY</u>	State	Zip <u>78150</u>	Country <u>FRANCE</u>
<b>NAME OF SECOND INVENTOR:</b>			
Given Name (first and middle [if any]) <u>Eric</u>		Family Name or Surname <u>BOUDJEMA</u>	
Inventor's Signature <u>[Signature]</u>		Date <u>X</u>	
Residence: City <u>BOULOGNE</u>	State	Country <u>France</u>	Citizenship <u>FRENCH</u>
Mailing Address: <u>80, rue Marcel Dassault</u>			
City <u>BOULOGNE</u>	State	Zip <u>92100</u>	Country <u>FRANCE</u>
<b>NAME OF THIRD INVENTOR:</b>			
Given Name (first and middle [if any]) <u>Denis</u>		Family Name or Surname <u>ROUFFET</u>	
Inventor's Signature <u>[Signature]</u>		Date <u>X 18/01/2002</u>	
Residence: City <u>BOULOGNE</u> <u>BILLANCOURT</u>	State	Country <u>France</u> <u>FR</u>	Citizenship <u>FRENCH</u>
Mailing Address: <u>16, rue Louis Pasteur</u>			
City <u>BOULOGNE</u> <u>BILLANCOURT</u>	State	Zip <u>92100</u>	Country <u>FRANCE</u>
<b>NAME OF FOURTH INVENTOR:</b>			
Given Name (first and middle [if any]) <u>Jean-Luc</u>		Family Name or Surname <u>PALMADE</u>	
Inventor's Signature <u>[Signature]</u>		Date <u>X</u>	
Residence: City <u>SAINT JORY</u>	State	Country <u>France</u>	Citizenship <u>FRENCH</u>
Mailing Address: <u>14A, Chemin de la Plaine</u>			
City <u>SAINT JORY</u>	State	Zip <u>31790</u>	Country <u>FRANCE</u>
<b>NAME OF FIFTH INVENTOR:</b>			
Given Name (first and middle [if any]) <u>Pascal</u>		Family Name or Surname <u>PIAU</u>	
Inventor's Signature <u>[Signature]</u>		Date <u>X</u>	
Residence: City <u>LACROIX</u> <u>FALGARDE</u>	State	Country <u>France</u>	Citizenship <u>FRENCH</u>
Mailing Address: <u>71, Route de la Gleyzette</u>			
City <u>LACROIX FALGARDE</u>	State	Zip <u>31120</u>	Country <u>FRANCE</u>
<b>NAME OF SIXTH INVENTOR:</b>			
Given Name (first and middle [if any]) <u>Yves</u>		Family Name or Surname <u>PELIGRY</u>	
Inventor's Signature <u>[Signature]</u>		Date <u>X</u>	

00019937 121000


<b>NAME OF SOLE OR FIRST INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Guillaume</b>		Family Name or Surname <b>CALOT</b>	
Inventor's Signature 		Date <b>X</b>	
Residence: City <b>LE CHESNAY</b>	State	Country <b>FRANCE</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>15, avenue de Villars</b>			
City <b>LE CHESNAY</b>	State	Zip <b>78150</b>	Country <b>FRANCE</b>
<b>NAME OF SECOND INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Eric</b>		Family Name or Surname <b>BOUDJEMA</b>	
Inventor's Signature 		Date <b>X</b>	
Residence: City <b>BOULOGNE</b>	State	Country <b>France</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>80, rue Marcel Dassault</b>			
City <b>BOULOGNE</b>	State	Zip <b>92100</b>	Country <b>FRANCE</b>
<b>NAME OF THIRD INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Denis</b>		Family Name or Surname <b>ROUFFET</b>	
Inventor's Signature 		Date <b>X</b>	
Residence: City <b>BOULOGNE</b> <b>BILLANCOURT</b>	State	Country <b>France</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>16, rue Louis Pasteur</b>			
City <b>BOULOGNE</b> <b>BILLANCOURT</b>	State	Zip <b>92100</b>	Country <b>FRANCE</b>
<b>NAME OF FOURTH INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Jean-Luc</b>		Family Name or Surname <b>PALMADE</b>	
Inventor's Signature 		Date <b>X 23/01/2002</b>	
Residence: City <b>FAYENCE</b> <b>SAINT-JORY</b>	State	Country <b>France</b> <b>FRX</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>44A, Chemin de la Plaine 13 Hameau de la Blanquarie</b>			
City <b>FAYENCE</b> <b>SAINT-JORY</b>	State	Zip <b>31790 83440</b>	Country <b>FRANCE</b>
<b>NAME OF FIFTH INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Pascal</b>		Family Name or Surname <b>PIAU</b>	
Inventor's Signature 		Date <b>X</b>	
Residence: City <b>LACROIX</b> <b>FALGARDE</b>	State	Country <b>France</b>	Citizenship <b>FRENCH</b>
Mailing Address: <b>71, Route de la Gleyzette</b>			
City <b>LACROIX FALGARDE</b>	State	Zip <b>31120</b>	Country <b>FRANCE</b>
<b>NAME OF SIXTH INVENTOR:</b>			
Given Name (first and middle [if any]) <b>Yves</b>		Family Name or Surname <b>PELIGRY</b>	
Inventor's Signature 		Date <b>X</b>	

4700


**NAME OF SOLE OR FIRST INVENTOR:**

Given Name (first and middle [if any]) **Guillaume** Family Name or Surname **CALOT**  
 Inventor's Signature  Date **X**  
 Residence: City **LE CHESNAY** State Country **FRANCE** Citizenship **FRENCH**  
 Mailing Address: **15, avenue de Villars**  
 City **LE CHESNAY** State Zip **78150** Country **FRANCE**


**NAME OF SECOND INVENTOR:**

Given Name (first and middle [if any]) **Eric** Family Name or Surname **BOUDJEMA**  
 Inventor's Signature  Date **X**  
 Residence: City **BOULOGNE** State Country **France** Citizenship **FRENCH**  
 Mailing Address: **80, rue Marcel Dassault**  
 City **BOULOGNE** State Zip **92100** Country **FRANCE**


**NAME OF THIRD INVENTOR:**

Given Name (first and middle [if any]) **Denis** Family Name or Surname **ROUFFET**  
 Inventor's Signature  Date **X**  
 Residence: City **BOULOGNE BILLANCOURT** State Country **France** Citizenship **FRENCH**  
 Mailing Address: **16, rue Louis Pasteur**  
 City **BOULOGNE BILLANCOURT** State Zip **92100** Country **FRANCE**


**NAME OF FOURTH INVENTOR:**

Given Name (first and middle [if any]) **Jean-Luc** Family Name or Surname **PALMADE**  
 Inventor's Signature  Date **X**  
 Residence: City **SAINT JORY** State Country **France** Citizenship **FRENCH**  
 Mailing Address: **14A, Chemin de la Plaine**  
 City **SAINT JORY** State Zip **31790** Country **FRANCE**

**NAME OF FIFTH INVENTOR:**

Given Name (first and middle [if any]) **Pascal** Family Name or Surname **PIAU**  
 Inventor's Signature  Date **X 17/01/02**  
 Residence: City **LACROIX FALGARDE** State Country **France** Citizenship **FRENCH**  
 Mailing Address: **71, Route de la Gleyzette**  
 City **LACROIX FALGARDE** State Zip **31120** Country **FRANCE**

**NAME OF SIXTH INVENTOR:**

Given Name (first and middle [if any]) **Yves** Family Name or Surname **PELIGRY**  
 Inventor's Signature  Date **X**

## French Language Declaration

Nom complet du troisième co-inventeur, le cas échéant	Full name of third joint inventor, if any (First Middle Last) Denis ROUFFET
Signature du troisième l'inventeur	Third inventor's signature
Date	Date
Domicile	Residence 16, rue Louis Pasteur 92100 BOULOGNE BILLANCOURT, FRANCE
Nationalité	Citizenship French
Adresse postale	Post Office Address 16, rue Louis Pasteur 92100 BOULOGNE BILLANCOURT, FRANCE
Nom complet du quatrième co-inventeur, le cas échéant	Full name of fourth joint inventor, if any (First Middle Last) Jean-Luc PALMADE
Signature du quatrième l'inventeur	Fourth inventor's signature
Date	Date
Domicile	Residence 14A, Chemin de la Plaine 31790 SAINT JORY, FRANCE
Nationalité	Citizenship French
Adresse postale	Post Office Address 14A, Chemin de la Plaine 31790 SAINT JORY, FRANCE
Nom complet du cinquième co-inventeur, le cas échéant	Full name of fifth joint inventor, if any (First Middle Last) Pascal PIAU
Signature du cinquième l'inventeur	Fifth inventor's signature
Date	Date
Domicile	Residence 71, Route de la GLEYZETTE 31120 LACROIX FALGARDE, FRANCE
Nationalité	Citizenship French
Adresse postale	Post Office Address 71, Route de la GLEYZETTE 31120 LACROIX FALGARDE, FRANCE
Nom complet du sixième co-inventeur, le cas échéant	Full name of sixth joint inventor, if any (First Middle Last) Yves PELIGRY
Signature du sixième l'inventeur	Sixth inventor's signature
Date	Date 02-02
Domicile	Residence 16, rue Saint Antoine 75004 PARIS, FRANCE
Nationalité	Citizenship French
Adresse postale	Post Office Address 16, rue Saint Antoine 75004 PARIS, FRANCE